



# Gap-Seal

## Water Based Acrylic Gap Sealant

### Description

SA Gap-Seal Acrylic Gap Sealant is a flexible, one part, water based acrylic latex caulk for interior and exterior gaps and joints.

### Key performance Properties

- One part ready to use
- Paintable
- Water based / water clean-up
- 5 Star VOC compliant

### Applications

SA Gap-Seal displays excellent adhesion to concrete, masonry, wood, brick, plasterboard and interior cornices. Gap-Seal is ideal for sealing interior and exterior wall joints not subjected to significant joint movement or pooling of water.

### Specifications

Typical data values should not be used as specifications.

**PART NO. GE91A Carton qty 20**

**\$2.06**  
+ GST ea  
**\$2.27 inc GST**

Property	Value
Colour	White
Specific Gravity	1.65 g/ml
Solids	85%
Application Temperature	5-40 °C
Shore A Hardness	40
100% Modulus	0.7 Mpa
Elongation At Break	200%
Skin Time -20°C/55%Rh	5 Minutes
Joint Movement Capability	±7.5%

Valid 31st March 2019 only while stocks last. Freight charges apply where applicable, errors & omissions excepted

[www.heatleys.com.au](http://www.heatleys.com.au)

**CANNING VALE** 50 Vinnicombe Drive T: 08 9256 5200 E: sales@heatleys.com.au

**BASSEDEAN** Unit 1 / 16 Dyer Road T: 08 6363 7373

**KALGOORLIE** 149 Boulder Road

T: 08 9091 0900

**BUNBURY** 53 McCombe Road T: 08 9724 2300

**WINGFIELD SA** 8 Lafitte Road

T: 08 7221 7221